

# DI-30 Series

## Weighing Indicator



- **Fluorescent display**
- **Connect with remote display**
- **Standard RS-232C interface**
- **Display resolution 1/20000(max.)**



DI-30N



DI-30SS

**DI-30 Series**  
Weighing indicator

# User-friendly features make it suitable to a wide range of weighing applications



DI-30N With Remote Display

Optional remote display



DI-30SS

- Display resolution 1/1000~1/20000
- Value tare and one touch tare
- Weight accumulated
- RS232 I/F
- Weight unit conversion(kg/lb)
- Accumulated modification
- Power for four 350Ω load cells
- IP 68 Protection (DI-30SS)

## Specifications

### Analog section:

Sensitivity range	1mV/V~3.5mV/V
Internal resolution	Max. 1/100000(fixed)
Apply Voltage	12VDC
Non linearity	<0.016% F.S
Number of load cells	Max.4 load cells(350Ω)

### Digital section:

Display	5 <sup>1/2</sup> digits
Indicator marks	"Zero", "Tare", "Stable", "Kg", "Lb", "Memory"

### General:

Power source	AC220/230/240V AC100/120V (-15% ~ +10%) 50/60Hz
Operation temperature	0°C ~ 40°C
Operation humidity	15% ~ 85%RH(No condensing)
Dimensions	200 × 130 × 180mm

### Options:

- All platforms of Teraoka
- Floor scale
- Optional remote display (DI-30N)

\*Specifications are subject to change without notice.

## TERAOKA SEIKO CO.,LTD

13-12 KUGAHARA 5-CHOME, OHTA-KU, TOKYO 146 JAPAN  
TEL:+81-3-3752-2131 FAX:+81-3-3752-2801