

DI-1100 Series

Weighing Indicator



- ▲ **Large LED display**
- ▲ **High internal resolution 1/100000**
- ▲ **Display resolution up to 1/10000**
- ▲ **RS232C I/F**

DI-1100 Series
Weighing Indicator

DI-1100 Series

Weighing Indicator

With style flexibility, a wide range of scale platforms sizes and capacities and PC link capability



Specifications

Analog section

Input sensitivity:	1mV/V – 3.5mV/V
Zero adj.range:	-10% to +100% of F.S.
Load cell excitation:	5VDC
A/D conversion rate:	6 times/sec.at 1mV/V output.
Temp.Coefficient:	ZERO: $\pm (0.2 \mu V \pm 5ppm \text{ of zero voltage}) / ^\circ C$ TYP SPAN: $\pm 5ppm / ^\circ C$ TYP
Non linearity:	0.008%F.S or less
Number of load cells:	Max.4x350 Ω

Digital section

Display:	6 digits LED display
Display division:	1,2,5,10,20,50,100,200
Decimal point location:	0,00000 to 000000
Indicator marks:	Zero,Net,Stable,Memory,Hold,kg/Lb

General

Power source:	AC/DC adaptor 12V 300 mA
Power consumption:	5W
Operating temperature:	-10 $^\circ C$ to 40 $^\circ C$
Operating Humidity:	15-85%RH (Non-condensing)
Dimensions:	195x86x60mm(Without support)

Interface: RS – 232C(option)



S-GA

Weighing Max:60\150\300(kg)
Platform Dimensions:360 x 480mm
Dimensions:360(W) x 480(D) x 96(H)mm
* Full Stainless Steel (optional)

*Specifications are subject to change without notice.

TERAOKA SEIKO CO.,LTD.

13 12 KUGAHARA 5 CHOME OHTA KU,
TOKYO 146-8580 JAPAN
TEL:+81-3-3752-2131 FAX:+81-3-3752-2801